

CRYOGENIC VALVE SERIES

超低温阀门系列

设计标准: GB/T24925

尺寸: 1/2" 到 48" (DN15 到 DN1200)

压力: 150LB 到 2500LB 16公斤到420公斤

材质: 碳钢, 不锈钢, 其他

操作: 手柄, 蜗轮, 电动, 气动

特殊: 逸散性要求、抗H₂S介质要求、海底球阀、低温球阀

Design Standard: GB/T 24925

Size: 1/2" to 48" (DN15 to DN1200)

Class: 150LB to 2500LB (16 bar to 420 bar)

Material: Carbon Steel, Stainless Steel, others

Operation: Lever, Gear, Electric, Pneumatic

Special: Fugitive Emission Valve, Re-H₂S Environment Valve, Subsea Ball Valve, Cryogenic Ball Valve.



锻钢低温加长杆固定式球阀
Forged Steel Cryogenic
Extended Stem Trunnion Ball Valve

CRYOGENIC VALVE SERIES

超低温阀门系列



低温蝶阀
Cryogenic
Butterfly Valve



低温上装式焊接球阀
Cryogenic Extended Stem
Welded Trunnion Ball Valve



低温闸阀
Cryogenic
Gate Valve



低温截止阀
Cryogenic
Globe Valve



锻钢截止阀
Cryogenic
Globe Valve



低温旋启式止回阀
Cryogenic
Swing Check Valve

